



STANDARD CONSTRUCTION

MODEL: A-DBE-04-3E8T-E
 FRAME: .081" THK. EXTRUDED ALUM. 6063-T5
 BLADES: .081" THK. EXTRUDED ALUM. 6063-T5
 BLADE AXLES AND BEARINGS:
 7/16" PLATED HEX AND BRONZE OILITE BUSHING
 LINKAGE: PLATED STEEL CONCEALED IN JAMB
 SEALS: VINYL BLADE AND ALUM. JAMB SEALS
 FASTENERS: #10-16 X 1" PLTD. STL. TEK SCREW
 SCREEN: 3/4" X .050 EXPD. ALUM. IN FRAME
 FINISH: TBD
 OPERATOR: SIEMENS GGD221.IU (120) Vac

NOTES:

1. ALL LOUVERS TO BE FABRICATED 1/4" UNDER LISTED OPNG. SIZES UNLESS SPECIFIED "ACTUAL".
2. ALL OPNG SIZES TO BE FIELD VERIFIED AND GUARANTEED BY OTHERS PRIOR TO FABRICATION.
3. OTHER SURROUNDING FINISHES ARE FOR REFERENCES ONLY AND TO BE SUPPLIED BY OTHERS.

LOUVER SCHEDULE

TAG QTY OPNG SIZE (WXH) NOTES

ADJUSTABLE LVR.
 W/ DIRECT DRIVE
 ACTUATOR

		DEPENDABLE PRODUCTS SINCE 1955	
		1855 SOUTH 54TH AVENUE, CICERO, IL. 60650	
ARCH/ENGR:		CUSTOMER:	
REV.		PROJECT:	
DESCRIPTION		DATE:	
DATE:		DRAWN: JN	
DATE:		CHKD: JN	
TITLE:		DRWG #:	
ADBE-04/SERIES			