



STANDARD CONSTRUCTION  
 MODEL: UFC-08-2Q0N-E  
 FRAME: .080" THK. FORMED ALUMINUM  
 (5005-H34)  
 BLADES: .080" THK. FORMED ALUMINUM  
 (5005-H34)  
 INTERIOR BLADES: 22 GA. GALV. PERF.  
 FASTENED TO BLADE UNDERSIDE  
 INSULATION: 6# DENSITY PCF MINERAL WOOL  
 FASTENERS: STEEL RIVETS EXPOSED  
 TO VIEW  
 SCREEN: EXPANDED ALUM. X .050" THK.  
 BIRDSCREEN IN FRAME  
 FINISH: KYNAR 500 2-STEP COLOR AS SELECTED

- NOTES:
1. ALL LOUVERS TO BE FABRICATED 1/4" UNDER LISTED OPNG. SIZES
  2. ALL OPENING SIZES TO BE FIELD VERIFIED AND GUARANTEED BY OTHER PRIOR TO FABRICATION
  3. OTHER SURROUNDING FINISHES ARE FOR REFERENCES ONLY TO BE SUPPLIED BY OTHERS.
  4. SUPPORTS ALL LOUVERS WITH MTG. CLIPS OR APPROVED EQ. @ 24" OC.

SECTION-A

SECTION-B

**SAFE AIR**  **DOWCO**  DEPENDABLE PRODUCTS SINCE 1965  
 1855 SOUTH 54TH AVENUE, CICERO, IL. 60650

ARCH/ENGR: \_\_\_\_\_ CUSTOMER: \_\_\_\_\_

REV.	DESCRIPTION	DATE	BY	PROJECT:	TITLE:
					UFC-08/SERIES
				DATE:	DRAWN:
				CHKD:	DRWG #: